

Roller bearing NQ30-30-JTEKT - NQ30-30-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nq30-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-------|-------|-------|-------------------------|-----------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 30 | — | 40 | 30 | 33.5 | 58.5 | 15 000 | NQ30/30 | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | — | | |
| | d_1 | D_1 | r_1 | 0.099 | — | — | | |
| | min. | max. | max. | — | — | — | | |
| | — | 38 | 0.3 | — | — | — | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952482651 |
| Inside diameter | 30 mm |
| Outside diameter | 40 mm |
| Thickness | 30 mm |
| Weight | 99 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE