


## Needle roller bearing NQI30-20-JTEKT - NQI30-20-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nqi30-20-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.		
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.	Without inner ring	Without inner ring		
35	30	45	20	—	0.3	24.7	41.4	13 000	—		
Mounting dimensions (mm)				Reference Mass (kg)		Applicable inner ring No.					
With inner ring				d <sub>1</sub> max.	D <sub>1</sub> max.	r <sub>1</sub> max.	Without inner ring	With inner ring			
NQI30/20				32	43	0.3	—	0.108			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482866
Inside diameter	30 mm
Outside diameter	45 mm
Thickness	20 mm
Weight	108 g
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE