

Roller bearing NQ40-30-JTEKT - NQ40-30-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nq40-30-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	B ₁	C _r	C _{10r}	Oil lub.	Without inner ring	
40	35	50	30	—	39.8	79.8	12 000	NQ40/30	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d _s min.	D _s max.	r _s max.	Without inner ring	With inner ring	
				37	48	0.3	0.120	0.192	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483054
Inside diameter	40 mm
Outside diameter	50 mm
Thickness	30 mm
Weight	120 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE