

## Roller bearing 40NQ5230-JTEKT - 40NQ5230-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/40nq5230-jtekt>

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.		Without inner ring	
40	—	52	30	—	47.0	81.0	11 000	40NQ5230	
		Mounting dimensions (mm)			Weight (kg)		Applicable inner ring No.		
With inner ring		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring			
		min.	max.	max.	—	—			
		—	48	0.8	0.148	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483085
Inside diameter	40 mm
Outside diameter	52 mm
Thickness	30 mm
Weight	148 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE