

Roller bearing NQS55-22-JTEKT - NQS55-22-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nqs55-22-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
55	45	72	22	44.6	71.6	8 300	NQS55/22	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	d_a	D_a	r_a	0.210	0.341			
	max.	max.	max.					
	49	66	0.6					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483504
Inside diameter	55 mm
Inside diameter	2.165" inch
Outside diameter	72 mm
Outside diameter	2.835" inch
Thickness	22 mm
Thickness	0.866" inch
Weight	210 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE