


## Roller bearing RNA6910-JTEKT - RNA6910-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/rna6910-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
58	50	72	40	74.0	140.0	7 900	<b>RNA6910</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d <sub>2</sub>	D <sub>2</sub>	r <sub>2</sub>	0.291	0.497	IRMS05040		
	min.	max.	max.					
	54	68	0.6					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483580
Inside diameter	58 mm
Inside diameter	2.283" inch
Outside diameter	72 mm
Outside diameter	2.835" inch
Thickness	40 mm
Thickness	1.575" inch
Weight	291 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE