

## Roller bearing NQ60-25-JTEKT - NQ60-25-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/roller/nq60-25-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
60	—	72	25	45.4	97.3	7 900	<b>NQ60/25</b>	
		Mounting dimensions (mm)			[Refer.] Mass (kg)		[Refer.] Applicable inner ring No.	
With inner ring		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring		
		min.	max.	max.	—	—		
		—	68	0.8	0.164	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483603
Inside diameter	60 mm
Outside diameter	72 mm
Thickness	25 mm
Weight	164 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE