

Deep groove ball bearing single row 694-ZZ-JTEKT - 694-ZZ-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/694-zz-jtekt>

Boundary dimensions

Open type Shielded Sealed Locating snap ring

ZZ / 2RS / 2RZ NR

694 / 695 / 600 / 602 / 630 / 632 / 634 / 636 / 640 / 642 / 644 / 646 / 648 / 650 / 652 / 654 / 656 / 658 / 660 / 662 / 664 / 666 / 668 / 670 / 672 / 674 / 676 / 678 / 680 / 682 / 684 / 686 / 688 / 690 / 692 / 694 / 696 / 698 / 700 / 702 / 704 / 706 / 708 / 710 / 712 / 714 / 716 / 718 / 720 / 722 / 724 / 726 / 728 / 730 / 732 / 734 / 736 / 738 / 740 / 742 / 744 / 746 / 748 / 750 / 752 / 754 / 756 / 758 / 760 / 762 / 764 / 766 / 768 / 770 / 772 / 774 / 776 / 778 / 780 / 782 / 784 / 786 / 788 / 790 / 792 / 794 / 796 / 798 / 800 / 802 / 804 / 806 / 808 / 810 / 812 / 814 / 816 / 818 / 820 / 822 / 824 / 826 / 828 / 830 / 832 / 834 / 836 / 838 / 840 / 842 / 844 / 846 / 848 / 850 / 852 / 854 / 856 / 858 / 860 / 862 / 864 / 866 / 868 / 870 / 872 / 874 / 876 / 878 / 880 / 882 / 884 / 886 / 888 / 890 / 892 / 894 / 896 / 898 / 900 / 902 / 904 / 906 / 908 / 910 / 912 / 914 / 916 / 918 / 920 / 922 / 924 / 926 / 928 / 930 / 932 / 934 / 936 / 938 / 940 / 942 / 944 / 946 / 948 / 950 / 952 / 954 / 956 / 958 / 960 / 962 / 964 / 966 / 968 / 970 / 972 / 974 / 976 / 978 / 980 / 982 / 984 / 986 / 988 / 990 / 992 / 994 / 996 / 998 / 1000

ML Extra-small: 6900 / 6902 / 6904 / 6906 / 6908 / 6910 / 6912 / 6914 / 6916 / 6918 / 6920 / 6922 / 6924 / 6926 / 6928 / 6930 / 6932 / 6934 / 6936 / 6938 / 6940 / 6942 / 6944 / 6946 / 6948 / 6950 / 6952 / 6954 / 6956 / 6958 / 6960 / 6962 / 6964 / 6966 / 6968 / 6970 / 6972 / 6974 / 6976 / 6978 / 6980 / 6982 / 6984 / 6986 / 6988 / 6990 / 6992 / 6994 / 6996 / 6998 / 7000

Extra-small (shielded) ZZ

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load limit (kN)		Factor	Limiting speeds (min-1)
	d	D	B	r (min)	C _r	C _{0r}	C _u	f ₀		
694 ZZ	4	11	4	0.15	1.2	0.35	9	124		Grease lub. 54000

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060623041
Inside diameter	4 mm
Sealing	-
Outside diameter	11 mm
Thickness	4 mm
Limiting speed	54000 rpm
Weight	1 g
Dynamic load	1.2 kN
Static load	0.35 kN
Packaging	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE