

Deep groove ball bearing single row WML5008-ZZ-JTEKT - WML5008-ZZ-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/wml5008-zz-jtekt>

Boundary dimensions

Open type Shielded Sealed Locating snap ring

ZZ / ZRU / ZRS / ZRD NR

800 / 850 / 900 / 950 / 1000 / 1100 / 1200 / 1300 / 1400 / 1500 / 16000 / 18000 / 20000 / 22000 / 24000 / 26000 / 28000 / 30000 / 32000 / 34000 / 36000 / 38000 / 40000 / 42000 / 44000 / 46000 / 48000 / 50000 / 52000 / 54000 / 56000 / 58000 / 60000 / 62000 / 64000 / 66000 / 68000 / 70000 / 72000 / 74000 / 76000 / 78000 / 80000 / 82000 / 84000 / 86000 / 88000 / 90000 / 92000 / 94000 / 96000 / 98000 / 100000

Extra small Standard shielded ZZ

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load limit (kN)		Factor	Limiting speeds (min-1)
	d	D	B	r (min)	Cr	C0r	Cu	f0		
WML5008 ZZ	5	8	2.5	0.05	0.27	0.09	2	15.7		59000

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060623089
Inside diameter	5 mm
Sealing	Shield on both sides
Outside diameter	8 mm
Thickness	2.5 mm
Limiting speed	59000 rpm
Dynamic load	0.27 kN
Static load	0.09 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE