

Deep groove ball bearing single row 682-JTEKT - 682-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/682-jtekt>

Boundary dimensions

Open type

Shielded

Sealed

Locating snap ring

ZZ / 2RS / 2RS / 2RD

NR

ISO 2818 / 2819 / 2820 / 2821 / 2822 / 2823 / 2824 / 2825 / 2826 / 2827 / 2828 / 2829 / 2830 / 2831 / 2832 / 2833 / 2834 / 2835 / 2836 / 2837 / 2838 / 2839 / 2840 / 2841 / 2842 / 2843 / 2844 / 2845 / 2846 / 2847 / 2848 / 2849 / 2850 / 2851 / 2852 / 2853 / 2854 / 2855 / 2856 / 2857 / 2858 / 2859 / 2860 / 2861 / 2862 / 2863 / 2864 / 2865 / 2866 / 2867 / 2868 / 2869 / 2870 / 2871 / 2872 / 2873 / 2874 / 2875 / 2876 / 2877 / 2878 / 2879 / 2880 / 2881 / 2882 / 2883 / 2884 / 2885 / 2886 / 2887 / 2888 / 2889 / 2890 / 2891 / 2892 / 2893 / 2894 / 2895 / 2896 / 2897 / 2898 / 2899

(M.L. Extra-small, minimum: 1000 / 1600 / 10000 / 6000 / 6200 / 6300 / 6400)

Extra-small standard open type

Bearing No.	Boundary dimensions (mm)					Basic load ratings (kN)		Fatigue load limit (kN)	factor	Limiting speeds (min-1)
	d	D	B	r (min)		Cr	COr	Cu	f0	Grease lub.
682	2	5	1.5	0.1		0.21	0.05	1	13.3	98000

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060623546
Inside diameter	2 mm
Outside diameter	5 mm
Thickness	1.5 mm
Limiting speed	98000 rpm
Dynamic load	0.21 kN
Static load	0.05 kN
Packaging	1

contact@123bearing.com
(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE