

Deep groove ball bearing single row 628-JTEKT - 628-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/628-jtekt>

Boundary dimensions

Open type Shielded Sealed Locating snap ring

ZE / 2RS / 2RS / 2RS
NR

160 / 165 / 170 / 175 / 180 / 185 / 190 / 195 / 200 / 205 / 210 / 215 / 220 / 225 / 230 / 235 / 240 / 245 / 250 / 255 / 260 / 265 / 270 / 275 / 280 / 285 / 290 / 295 / 300 / 305 / 310 / 315 / 320 / 325 / 330 / 335 / 340 / 345 / 350 / 355 / 360 / 365 / 370 / 375 / 380 / 385 / 390 / 395 / 400 / 405 / 410 / 415 / 420 / 425 / 430 / 435 / 440 / 445 / 450 / 455 / 460 / 465 / 470 / 475 / 480 / 485 / 490 / 495 / 500 / 505 / 510 / 515 / 520 / 525 / 530 / 535 / 540 / 545 / 550 / 555 / 560 / 565 / 570 / 575 / 580 / 585 / 590 / 595 / 600 / 605 / 610 / 615 / 620 / 625 / 630 / 635 / 640 / 645 / 650 / 655 / 660 / 665 / 670 / 675 / 680 / 685 / 690 / 695 / 700 / 705 / 710 / 715 / 720 / 725 / 730 / 735 / 740 / 745 / 750 / 755 / 760 / 765 / 770 / 775 / 780 / 785 / 790 / 795 / 800 / 805 / 810 / 815 / 820 / 825 / 830 / 835 / 840 / 845 / 850 / 855 / 860 / 865 / 870 / 875 / 880 / 885 / 890 / 895 / 900 / 905 / 910 / 915 / 920 / 925 / 930 / 935 / 940 / 945 / 950 / 955 / 960 / 965 / 970 / 975 / 980 / 985 / 990 / 995 / 1000

Extra small Standard open type

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)		factor f0	Limiting speeds(min-1) Grease lub.
	d	D	B	r (min)	Cr	Cor	Cu			
628	8	24	8	0.3	4.15	1.4	0.06	12.8	28000	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250300318
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	8 mm
Limiting speed	28000 rpm
Dynamic load	4.15 kN
Static load	1.4 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE