

Tapered roller bearing 30304-AC-JTEKT - 30304-AC-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30304-ac-jtekt>

Boundary dimensions

Single row	Double row	Four row
Normal gradation	Medium gradation	Double row (TDO type)
30304JR 30304KR 30304JR 30304KR 30304JR 30304KR 30304JR 30304KR 30304JR 30304KR 30304JR 30304KR	40304 40304 40304 40304 40304 40304 40304 40304 40304 40304 40304 40304	47304 47304 47304 47304 47304 47304 47304 47304 47304 47304 47304 47304
Single row with		Primarily for use in the roll necks of rolling mills

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load limit (kN)		Limiting speed (min ⁻¹)
	d	D	B	d ₁	C	C ₀	C ₁₀	C ₅₀	ISO
30304AC	20	52	16.25	16	43.3	28.4	4.65	4.65	8300

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060627490
Inside diameter	20 mm
Outside diameter	52 mm
Thickness	16.25 mm
Limiting speed	8300 rpm
Dynamic load	43.3 kN
Static load	28.4 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE