


Needle roller cage K25-37-20-H-JTEKT - K25-37-20-H-JTEKT

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/cage/k25-37-20-h-jtekt>

Boundary dimensions



Basic needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speed(min-1) | |
|-------------|-------------------------|----|----|------------------------|------|------------------------|-----------------------|----------|
| | Dw | Dw | Bc | Cr | Ctr | Ca | Grease lub. | Oil lub. |
| K25X37X20H | 25 | 37 | 20 | 32.5 | 34.1 | 5.45 | 12000 | 19000 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060634351 |
| Inside diameter | 25 mm |
| Outside diameter | 37 mm |
| Thickness | 20 mm |
| Limiting speed | 12000 rpm |
| Dynamic load | 32.5 kN |
| Static load | 34.1 kN |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE