

## Deep groove ball bearing single row 21306-RZ-JTEKT - 21306-RZ-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/21306-rz-jtekt>

Boundary dimensions

Asymmetrical rollers: R/R, R/RH, R/H  
Symmetrical rollers: R/RH, R/H  
Taper bore: Kort30

2390R / 2300RH/RH1 / 2300RH/RH2 / 2300RH/RH3 / 21306R / 2400RH/RH1 / 2400RH/RH2 / 2400RH/RH3 / 2400RH/RH4 / 2400RH/RH5 / 2400RH/RH6 / 2400RH/RH7 / 2400RH/RH8 / 2400RH/RH9 / 2400RH/RH10 / 2400RH/RH11 / 2400RH/RH12 / 2400RH/RH13 / 2400RH/RH14 / 2400RH/RH15 / 2400RH/RH16 / 2400RH/RH17 / 2400RH/RH18 / 2400RH/RH19 / 2400RH/RH20 / 2400RH/RH21 / 2400RH/RH22 / 2400RH/RH23 / 2400RH/RH24 / 2400RH/RH25 / 2400RH/RH26 / 2400RH/RH27 / 2400RH/RH28 / 2400RH/RH29 / 2400RH/RH30 / 2400RH/RH31 / 2400RH/RH32 / 2400RH/RH33 / 2400RH/RH34 / 2400RH/RH35 / 2400RH/RH36 / 2400RH/RH37 / 2400RH/RH38 / 2400RH/RH39 / 2400RH/RH40 / 2400RH/RH41 / 2400RH/RH42 / 2400RH/RH43 / 2400RH/RH44 / 2400RH/RH45 / 2400RH/RH46 / 2400RH/RH47 / 2400RH/RH48 / 2400RH/RH49 / 2400RH/RH50 / 2400RH/RH51 / 2400RH/RH52 / 2400RH/RH53 / 2400RH/RH54 / 2400RH/RH55 / 2400RH/RH56 / 2400RH/RH57 / 2400RH/RH58 / 2400RH/RH59 / 2400RH/RH60 / 2400RH/RH61 / 2400RH/RH62 / 2400RH/RH63 / 2400RH/RH64 / 2400RH/RH65 / 2400RH/RH66 / 2400RH/RH67 / 2400RH/RH68 / 2400RH/RH69 / 2400RH/RH70 / 2400RH/RH71 / 2400RH/RH72 / 2400RH/RH73 / 2400RH/RH74 / 2400RH/RH75 / 2400RH/RH76 / 2400RH/RH77 / 2400RH/RH78 / 2400RH/RH79 / 2400RH/RH80 / 2400RH/RH81 / 2400RH/RH82 / 2400RH/RH83 / 2400RH/RH84 / 2400RH/RH85 / 2400RH/RH86 / 2400RH/RH87 / 2400RH/RH88 / 2400RH/RH89 / 2400RH/RH90 / 2400RH/RH91 / 2400RH/RH92 / 2400RH/RH93 / 2400RH/RH94 / 2400RH/RH95 / 2400RH/RH96 / 2400RH/RH97 / 2400RH/RH98 / 2400RH/RH99 / 2400RH/RH100

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)	Limiting speeds(min-1)
	d	D	B	n(min)	Cr	C0r	C0	Grease lub.
21306RZ	30	72	19	1.1	74.2	62.7	4.8	7200

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060661524
Inside diameter	30 mm
Outside diameter	72 mm
Thickness	19 mm
Limiting speed	7200 rpm
Dynamic load	74.2 kN
Static load	62.7 kN
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE