

Deep groove ball bearing single row 24148-RR-JTEKT - 24148-RR-JTEKT

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/24148-rr-jtekt>

Boundary dimensions

Asymmetrical rollers: R, RR
Symmetrical rollers: F, FR, R, RH
Taper bore: K, KR

2390R / 2300R(RH) / 2310R(RH) / 2320R(RH) / 2330R(RH) / 2340R(RH) / 2350R(RH) / 2360R(RH) / 2370R(RH) / 2380R(RH) / 2390R(RH) / 2400R(RH) / 2410R(RH) / 2420R(RH) / 2430R(RH) / 2440R(RH) / 2450R(RH) / 2460R(RH) / 2470R(RH) / 2480R(RH) / 2490R(RH) / 2500R(RH)

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)	Limiting speeds(min-1)
	d	D	B	r (min)	Cr	C0r	C0r Grease lub.	
24148RR	240	400	160	4	2640	3850	287	800

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060670861
Inside diameter	240 mm
Outside diameter	400 mm
Thickness	160 mm
Limiting speed	800 rpm
Dynamic load	2640 kN
Static load	3850 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE