

**Roller chain simplex**  
**ANSI120-1HV-ELITE-5M-IWIS - ANSI120-1HV-ELITE-5M-IWIS**

<https://www.123bearing.com/power-transmission/roller-chain/simplex/ansi120-1hv-elite-5m-iwis>



**PRODUCT FEATURES**

Brand	IWIS
N° Ean13	3616060998972
Type	120
Lubrication	elidurplus
Packaging	5m
Series	HV
Chain standards	iso606ansi
ISO standard breaking load	182.4 kN
Weight per meter	6.6 kg
Joint surface	4.13 cm <sup>2</sup>
Pitch	38.1 mm
Pitch	1 1/2" inch
Width between inner plates	25.22 mm
Width between inner plates	0.993" inch
Roller diameter	22.23 mm
Roller diameter	7/8" inch
Axis diameter	11.11 mm
Axis diameter	7/16" inch
Plate thickness inside outside	5,6
Plate height	36.2 mm
Plate height	1.425" inch
Additional length	6.6 mm
Additional length	0.26" inch
number of rows	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE