


Deep groove ball bearing single row 7212-B-XL-2RS-TVP-FAG - 0227532810000

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/0227532810000>

Angular contact ball bearings 7212-B-2RS-TVP
main dimensions to DIN 625-1, contact angle $\alpha = 40^\circ$, lip seats on both sides



d	60 mm
D	110 mm
B	22 mm
a	47 mm
D ₂	94.4 mm
D ₃	103.4 mm
D ₄ max	101 mm
D ₅ max	104.4 mm
d ₂	80.3 mm
d ₃ min	89 mm
r ₁ max	1.5 mm
r ₂ max	1.5 mm
r ₃ max	1.5 mm
r ₄ max	1.5 mm
r ₅ max	1.5 mm
r ₆ max	1.5 mm
r ₇ max	1.5 mm
r ₈ max	1.5 mm
r ₉ max	1.5 mm
r ₁₀ max	1.5 mm
r ₁₁ max	1.5 mm
r ₁₂ max	1.5 mm
r ₁₃ max	1.5 mm
r ₁₄ max	1.5 mm
r ₁₅ max	1.5 mm
r ₁₆ max	1.5 mm
r ₁₇ max	1.5 mm
r ₁₈ max	1.5 mm
r ₁₉ max	1.5 mm
r ₂₀ max	1.5 mm
r ₂₁ max	1.5 mm
r ₂₂ max	1.5 mm
r ₂₃ max	1.5 mm
r ₂₄ max	1.5 mm
r ₂₅ max	1.5 mm
r ₂₆ max	1.5 mm
r ₂₇ max	1.5 mm
r ₂₈ max	1.5 mm
r ₂₉ max	1.5 mm
r ₃₀ max	1.5 mm
r ₃₁ max	1.5 mm
r ₃₂ max	1.5 mm
r ₃₃ max	1.5 mm
r ₃₄ max	1.5 mm
r ₃₅ max	1.5 mm
r ₃₆ max	1.5 mm
r ₃₇ max	1.5 mm
r ₃₈ max	1.5 mm
r ₃₉ max	1.5 mm
r ₄₀ max	1.5 mm
r ₄₁ max	1.5 mm
r ₄₂ max	1.5 mm
r ₄₃ max	1.5 mm
r ₄₄ max	1.5 mm
r ₄₅ max	1.5 mm
r ₄₆ max	1.5 mm
r ₄₇ max	1.5 mm
r ₄₈ max	1.5 mm
r ₄₉ max	1.5 mm
r ₅₀ max	1.5 mm
r ₅₁ max	1.5 mm
r ₅₂ max	1.5 mm
r ₅₃ max	1.5 mm
r ₅₄ max	1.5 mm
r ₅₅ max	1.5 mm
r ₅₆ max	1.5 mm
r ₅₇ max	1.5 mm
r ₅₈ max	1.5 mm
r ₅₉ max	1.5 mm
r ₆₀ max	1.5 mm
r ₆₁ max	1.5 mm
r ₆₂ max	1.5 mm
r ₆₃ max	1.5 mm
r ₆₄ max	1.5 mm
r ₆₅ max	1.5 mm
r ₆₆ max	1.5 mm
r ₆₇ max	1.5 mm
r ₆₈ max	1.5 mm
r ₆₉ max	1.5 mm
r ₇₀ max	1.5 mm
r ₇₁ max	1.5 mm
r ₇₂ max	1.5 mm
r ₇₃ max	1.5 mm
r ₇₄ max	1.5 mm
r ₇₅ max	1.5 mm
r ₇₆ max	1.5 mm
r ₇₇ max	1.5 mm
r ₇₈ max	1.5 mm
r ₇₉ max	1.5 mm
r ₈₀ max	1.5 mm
r ₈₁ max	1.5 mm
r ₈₂ max	1.5 mm
r ₈₃ max	1.5 mm
r ₈₄ max	1.5 mm
r ₈₅ max	1.5 mm
r ₈₆ max	1.5 mm
r ₈₇ max	1.5 mm
r ₈₈ max	1.5 mm
r ₈₉ max	1.5 mm
r ₉₀ max	1.5 mm
r ₉₁ max	1.5 mm
r ₉₂ max	1.5 mm
r ₉₃ max	1.5 mm
r ₉₄ max	1.5 mm
r ₉₅ max	1.5 mm
r ₉₆ max	1.5 mm
r ₉₇ max	1.5 mm
r ₉₈ max	1.5 mm
r ₉₉ max	1.5 mm
r ₁₀₀ max	1.5 mm
m	0.797 kg Mass
C	99000 N Basic dynamic load rating, radial
C ₀	45000 N Basic static load rating, radial
n ₁₂	3400 1/min Limiting speed
n ₂	- 1/min Reference speed
C ₁₀	3050 N Fatigue limit load, radial

PRODUCT FEATURES

Brand	FAG
N° Ean13	4012802001013
Inside diameter	60 mm
Sealing	Seal on both sides
Outside diameter	110 mm
Thickness	22 mm
Limiting speed	3450 rpm
Weight	795 g
Dynamic load	62 kN
Static load	45 kN
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE