


Drawn cup roller bearing BAM1210-IKO - BAM1210-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam1210-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 ($\frac{3}{4}$)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm(inch) Standard mounting dimensions mm Basic dynamic load rating C Basic static load rating C0 Allowable rotational speed(*) Assembled inner ring													
	F_w	D	C	$\frac{h6}{js7}$	Shaft dia. Max. Min.	Housing bore dia. Max. Min.							
	19.050 $\frac{3}{4}$	25.400 1	15.881 $\frac{5}{8}$	1.3	19.050 19.037	25.412 25.391	9 500	13 200	20 000	IRB #10-1			

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173009
Inside diameter	19.05 mm
Outside diameter	25.4 mm
Thickness	15.88 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE