


## Drawn cup roller bearing BAM1216-IKO - BAM1216-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam1216-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
19.050 ( $\frac{3}{8}$ )	---	---	---	---	---	BAM 1216	28.5	---

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. d <sub>h6</sub> Max.   Min.	Housing bore dia. J7 Max.   Min.	mm				
19.050   $\frac{3}{8}$	25.400   1	25.40   1.000   1.3	19.050   19.037	25.412   25.391	16 300	26 500	20 000	IRB 816-1	

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173030
Inside diameter	19.05 mm
Outside diameter	25.4 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE