


Drawn cup roller bearing BAM1312-IKO - BAM1312-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam1312-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	BAM 1312												
20.638 ($\frac{3}{16}$)	---	---	---	---	---	---	---	---	---	---	---	---	---

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	mm					
20.638 $\frac{3}{16}$	26.988 $1 \frac{1}{8}$	19.051 $\frac{3}{4}$	20.638 Max.	20.625 Min.	27.000 Max.	26.979 Min.	12 400	19 000	19 000	IRB 912

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173078
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	19.05 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE