


Drawn cup roller bearing BAM1716-IKO - BAM1716-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam1716-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
26.988 (1 1/8)	—	—	—	—	—	—	—	BAM 1716	40.5	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(*)	Assembled inner ring	
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t</i> Max.	Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	N	N	rpm	—	
26.988 1 1/8	33.338 1 1/4	25.40 1.000	2.8	26.988 26.975	33.352 33.327	20 000	38 900	14 000	—	—	

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173320
Inside diameter	26.99 mm
Outside diameter	33.34 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE