


Drawn cup roller bearing BAM208-IKO - BAM208-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam208-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																							
	Standard	Mass (Ref.) g	Closed end																																																	
31.750 (1 1/4)	---	---	---	---	---	---	---	---	---	---	---	---	---																																							
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th>Basic dynam. load rating</th> <th>Basic static load rating</th> <th>Allowable rotational speed(*)</th> <th>Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h₈/k₇</th> <th>Housing bore dia. J7/k6</th> <th>Max.</th> <th>Min.</th> <th>C</th> <th>C₀</th> <th>N</th> <th>N</th> <th>rpm</th> <th colspan="2"></th> </tr> </thead> <tbody> <tr> <td>31.750 (1 1/4)</td> <td>38.100 (1 1/2)</td> <td>12.70 (.500)</td> <td>2.8</td> <td>31.750 31.734</td> <td>38.114</td> <td>38.089</td> <td>9 100</td> <td>14 700</td> <td>12 000</td> <td colspan="2">IRB 168</td> <td colspan="2"></td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring	F _w	D	C	Shaft dia. h ₈ /k ₇	Housing bore dia. J7/k6	Max.	Min.	C	C ₀	N	N	rpm			31.750 (1 1/4)	38.100 (1 1/2)	12.70 (.500)	2.8	31.750 31.734	38.114	38.089	9 100	14 700	12 000	IRB 168			
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring																																										
F _w	D	C	Shaft dia. h ₈ /k ₇	Housing bore dia. J7/k6	Max.	Min.	C	C ₀	N	N	rpm																																									
31.750 (1 1/4)	38.100 (1 1/2)	12.70 (.500)	2.8	31.750 31.734	38.114	38.089	9 100	14 700	12 000	IRB 168																																										

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173405
Inside diameter	31.75 mm
Outside diameter	38.1 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE