


Drawn cup roller bearing BAM56-IKO - BAM56-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam56-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
7.938 ($\frac{5}{16}$)	—	—	—	—	—	—	—	BAM 56	3.9	—	—		
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	h_8	Max.	Min.	Max.	Min.	N	N	rpm			
7.938	12.700	9.521	7.938	7.929	12.710	12.692		2 620	2 390	45 000	—		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173443
Inside diameter	7.94 mm
Outside diameter	12.7 mm
Thickness	9.52 mm
Weight	3.9 g
Packaging	-
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE