

Drawn cup roller bearing BAM76-IKO - BAM76-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam76-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g			
11.112 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 76	5.3	—	—	
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	h_8 Max.	J_7 Max.	N Max.	N Min.	C_0 Max.	C_0 Min.	N	N	rpm	
11.112	15.875	9.521	0.375	1	11.112	11.101	15.885	15.867	3 290	3 470	35 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173535
Inside diameter	11.11 mm
Outside diameter	15.88 mm
Thickness	9.52 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE