


## Drawn cup roller bearing BAM78-IKO - BAM78-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/drawn-cup/bam78-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
11.112 ( $\frac{7}{16}$ )	—	—	—	—	—	—	<b>BAM 78</b>	7	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h8	Housing bore dia. J7	Min.	Max.				
11.112 ( $\frac{7}{16}$ )	15.875 ( $\frac{5}{8}$ )	12.70 (0.500)	11.112	11.101	15.885	15.867	4 460	5 130	35 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173559
Inside diameter	11.11 mm
Outside diameter	15.88 mm
Thickness	12.7 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE