

Housed bearing accessorie YSPAG207-SKF - YSPAG207-SKF

<https://www.123bearing.com/bearing-housing/housed-bearing/accessories/yspag207-skf>

Dimensions d'encastrement				Charges de base		Vitesse limite	Désignation
d	D	B ₁	C	dynamique C	statique C ₀	tr/min	
mm				kN			
35	72	39,5	19	25,5	15,3	3300	YSPAG 207

C19
 C₀ M5
 B₁ 39,5
 d₁ 48,1
 d₂ 57
 d 35
 C19
 C₀ M5
 B₁ 39,5
 d₁ 48,1
 d₂ 57
 d 35

Clé hexagonale (mm)
 Couple de serrage recommandé (Nm)
 7,4
 Douille caoutchouc appropriée
 RS 207 A
 Coefficient de calcul
 f₀ 14

Values for B₁ and d₁ before the grub screw is tightened
 (Sleeve and inner ring both at starting position)

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316574761647
Inside diameter	35 mm
Outside diameter	72 mm
Thickness	39.5 mm
Tightening	-
Weight	449 g
Packaging	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE