

## Deep groove ball bearing single row W6008-2RS1-SKF - W6008-2RS1-SKF

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/single-row/w6008-2rs1-skf>

Dimensions d'encastrement		Charges de base		Vitesses de base		Désignation
d	D	B	Dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite
40	68	15	14	10,8	-	6300
<p>Technical drawing showing two views of the bearing: a front view and a side view. Dimensions are labeled: d=40, D=68, B=15, D<sub>1</sub>=62.5, d<sub>1</sub>=49.2, r<sub>1,2min</sub>=1, r<sub>1,2max</sub>=1, D<sub>max</sub>=63.4, D<sub>min</sub>=62.6, r<sub>max</sub>, r<sub>min</sub>=44.6. Coefficients de calcul: k<sub>r</sub>=0,025, f<sub>g</sub>=15.</p>						

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316570648621
Inside diameter	40 mm
Inside diameter	1.575" inch
Sealing	Seal on both sides
Cage	Sheet metal
Radial class	CN
Outside diameter	68 mm
Outside diameter	2.677" inch
Thickness	15 mm
Thickness	0.591" inch
Limiting speed	6300 rpm
Weight	191 g
Dynamic load	14.6 kN
Static load	11.4 kN
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE