


Tapered roller bearing 2586-2525-TIMKEN - 2586-2525-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/2586-2525-timken>

TAPERED ROLLER BEARINGS												
SINGLE-ROW • TYPE TS												
TYPE TS												
												
Bearing Dimensions			Load Ratings						Part Number			
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽¹⁾ e	Dynamic ⁽¹⁾ C ₁₀	Factor ⁽¹⁾ K	Static C ₂	Inner	Outer			
mm	mm	mm	N		N		N					
30.000	72.022	23.812	63700	0.27	21700	10200	94000	2586	2525			
1.1811	2.8355	0.9375	18500		4680	2280	21200					
Bearing Dimensions												
SHAFT										HOUSING		
Width B	Width C	ER. Co. μm	Max Shaft Fillet Radius R _{fs}	Backing Shoulder Dia. d _s	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r _h	Backing Shoulder Dia. D _s	Backing Shoulder Dia. D _s	Cage	Geometry Factors		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	G ₁	G ₂	C ₃
25.257	19.050	-0.6	3.5	36.8	42.5	0.8	65.0	62.0	0.8	0.8	25.6	9.6
0.9943	0.7500	-0.24	0.14	1.42	1.67	0.03	2.56	2.48	0.03	0.04	0.9606	0.38

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952309224
Inside diameter	30 mm
Outside diameter	72.02 mm
Thickness	23.81 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE