


Tapered roller bearing 1674-1620-TIMKEN - 1674-1620-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/1674-1620-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer	
mm	mm	mm	N		N		N			
31.623	66.675	20.628	3250	0.37	1300	0.56	1700	1674	1620	
1.245	2.625	0.8125	1150		360		1300			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _f ⁽¹⁾	Backing Shoulder Dia. d _s ⁽¹⁾	Max Housing Fillet Radius r _f ⁽¹⁾	Backing Shoulder Dia. D _s ⁽¹⁾	A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	A ₁ ⁽²⁾	A ₂ ⁽²⁾	G ₁	G ₂	C ₁	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
20.628	15.875	-5.3	1.5	37.8	35.5	1.5	61.0	58.0	1.5	1.1	16.6	6.7	0.964	0.33
0.8125	0.625	-0.21	0.06	1.46	1.36	0.06	2.40	2.28	0.06	0.05				0.72

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952309941
Inside diameter	31.62 mm
Inside diameter	1.245" inch
Outside diameter	66.68 mm
Outside diameter	2 5/8" inch
Thickness	20.64 mm
Thickness	13/16" inch
Weight	200 g
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE