


## Tapered roller bearing 19138-19267X-TIMKEN - 19138-19267X-TIMKEN

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/19138-19267x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
34.976 1.3730	68.000 2.6772	16.019 0.6307	92700 11400	1.25	12100 2960	10000 2258	57000 13000	19138	19267X	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage		Geometry Factors			kg					
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>		A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
16.020 0.6304	12.000 0.4724	-1.5 -0.06	1.5 0.06	48.5 1.91	42.5 1.67	1.5 0.06	64.0 2.52	61.8 2.42	1.1 0.04	1.6 0.06	17.5	11.5	0.9804	0.26 0.57

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952310299
Inside diameter	34.98 mm
Outside diameter	68 mm
Thickness	16.02 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE